

[+🔍 Visa fler](#)**Produktfamilj****Fenzy Aeris Comfort SCBA**

Self Contained Breathing Apparatus designed for firefighting and Oil&Gas industries. It fulfills the requirements of the most recent EN 137 standard, type 2 classification.

Product Numbers & Ordering Information

	1814316	Fenzy Aeris Comfort SCBA - EN Standard Includes manometer with alarm whistle, medium size full face mask "Panoramasque" with silicone headstraps and "Fenzy Zenith" automatic demand valve, without cylinder
	1823231	Fenzy Aeris Comfort Type 2 SCBA - EN Standard Includes manometer with alarm whistle, medium size full face mask "Panoramasque" with silicone headstraps and "Fenzy Zenith" automatic demand valve, without cylinder

Ytterligare information

Please contact us at fenzy-info@sperianprotection.com or call +33149907979

Viktigaste egenskaperna

- Non-metallic auto-extinguishable and ergonomic back-plate

Översikt

- Three carry handles and an attachment point for a lifeline
- Comfort cushions on the shoulders and belt straps
- Perfect weight distribution of the apparatus on hips
- Compatible with a full range of EN compressed air cylinders from 4L/200 bar to 9L/300 bar
- Adjustable cylinder collar and twin-cylinder version with simple addition of a manifold kit
- Reducer with a built-in second user outlet
- Harness with aramide fibre straps: fulfills the requirements of the most recent EN 137 standard
- Fluorescent strips on shoulder and belt straps
- Pressure gauge whistle: located close to the ear
- HP/MP reducer with safety valve
- By-Pass button on lung demand valve
- Fenzy full face masks comply with EN 136 standard – Class III

Rekommenderade branscher/rekommenderat användningsområde

- Kemi
- Brandskydd
- Myndigheter
- Polis
- Tillverkning
- Olja och gas
- Stål och metaller

Risker

- Luftburna partiklar
- Biologiska risker
- Kemi
- Kontaminering
- Brand
- Gas, ånga, rök

Föreskrifter

- - • EN 137:2006 Type 2 • CE0194/0060 • ISO 9001 • Bureau Veritas for Marine use (SOLAS, MSC and MED)

Tidigare varumärke

Fenzy

Specifikationer

Homologations	EN 137:2006 Type 2, CE0194/0060, ISO 9001, Bureau Veritas for Marine use (SOLAS, MSC and MED)
Total weight of the complete apparatus without the cylinder	4.3 kg
Harness	Nomex® comfort cushions on the shoulder and belt straps.

Back-plate	Non-metallic auto-extinguishable and ergonomic
Cylinder pressure	200 or 300 bars
Medium pressure and maximum flow of the reducer	7.5 bars; >1200 litres/min
Consumption and activation of the audible alarm	Air consumption <5 litres; 55 bars

Including User's Manual

Training & Proper Use

fenzy-info@sperianprotection.com or call +33149907979

Ytterligare information

fenzy-info@sperianprotection.com or call +33149907979

Teknisk support

© Honeywell International Inc.